



KÖSTER Loka Handpump

Technical Data Sheet IN 952 001

Issued: 2015-04-24

Manually operated pump for pumping and injecting grouts

max. 12 l/min at max. 10 bar

approx. 14 kg

mm

approx. 500 mm x 200 mm x 1100

Features

The KÖSTER Loka Handpump is a reliable manually driven membrane pump which is suitable for pumping and injecting KÖSTER grouting mortars. This hand membrane pump is equipped with a surge tank and a removable lid, in which the manometer for pressure measurement is integrated. A sufficiently large dimensioned base plate ensures good stability during pumping. The length of the hand lever was chosen for ease of use. A pressure compensation of the discharge hose or pumping the material in a circuit can be achieved via a ball valve on the y-output piece of the pump. Any pistol or packer can be mounted onto the discharge hose.

Technical Data

Capacity:

Measurements:

Weight:

Fields of Application

Pumping and injecting of:

KÖSTER Micro Grout 1C

KÖSTER Mautrol Borehole Suspension

Substrate

Pre-wet the crack or substrate before pumping cementitious grouts.

Cleaning

Clean the pump immediately after use with clean water.

Packaging

IN 952 001

Safety

Wear goggles, gloves, and a long-sleeved shirt when working with cementitious materials. Use all Personal Protective Equipment required by governmental, state, and local regulations when processing the material.

piece



Related products

KÖSTER Micro Grout 1C KÖSTER Mautrol Borehole Suspension IN 295 024 M 150 024

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.

KÖSTER BAUCHEMIE AG • Dieselstr. 1-10 • D-26607 Aurich • Tel. 04941/9709-0 • Fax 04941/9709-40
E-Mail: info@koester.eu - Internet: www.koester.eu