



## KÖSTER KSK Primer BL

Technical Data Sheet W 120 015

Issued: 2015-05-05

### Solvent free, polymer-modified bitumen based strongly adhesive primer for KSK membranes and Polymer Modified Bitumen Coatings

#### Features

KÖSTER KSK Primer BL is a solvent free, polymer-modified bitumen based strongly adhesive primer for KSK membranes and Polymer Modified Bitumen Coatings. It is characterized by very good adhesion to dry and moist mineral substrates.

KÖSTER Fix-Tape 15 DS  
KÖSTER KSK ALU 15  
KÖSTER KSK SY 15  
KÖSTER KSK DS 15

Prod. code W 815 020 DS  
Prod. code W 815 096 AL  
Prod. code W 815 105  
Prod. code W 815 105 DS

#### Technical Data

Solid particle content	greater than 55 %
Minimum application temperature	+ 5 °C
Curing time (at + 20 °C)	24 hours
Application of next layer (at + 20 °C)	approx. 3 – 4 hours
(at + 10 °C)	approx. 5 – 7 hours

#### Fields of Application

KÖSTER KSK Primer BL is a primer for preparing substrates for the application of KÖSTER KSK membranes and KÖSTER Polymer Modified Bitumen Coatings such as KÖSTER Deuxan.

#### Substrate

The substrate has to be free of loose particles, dust, oil, and grease.

#### Application

KÖSTER KSK Primer BL is applied thoroughly undiluted in one coat using a roller, brush, or a suitable spraying device.

#### Consumption

approx. 0.25 - 0.4 kg/m<sup>2</sup>  
(in case of strongly absorbent substrates, two coats may be necessary – total consumption approx. 500 g / m<sup>2</sup>)

#### Cleaning

Clean tools immediately after use with clean water.

#### Packaging

W 120 015 15 kg bucket

#### Storage

Store the material cool but frost free. In originally sealed containers it can be stored for a minimum of 12 months.

#### Safety

Observe all governmental, state, and local safety regulations when processing the material.

#### Related products

KÖSTER Special Joint Tape	Prod. code J 870 010
KÖSTER KSK ALU Strong	Prod. code R 817 105 AS
KÖSTER Fix-Tape 10 SY	Prod. code W 810
KÖSTER Fix-Tape 10 ALU	Prod. code W 810 AL
KÖSTER Butyl Fix-Tape Fleece	Prod. code W 815 015 F

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.